



# Midea MVMP Series Air Handler

MVMP Series

Cooling capacity: 18-60 kBtu/h



## Contents:


1 PRODUCT LINEUP.....	2
2 NOMENCLATURE.....	2
3 SPECIFICATIONS.....	3
4 DIMENSIONAL DRAWING.....	5
5 ELECTRICAL CHARACTERISTICS.....	6
6 AIRFLOW DATA.....	9
7 ACCESSORIES.....	11
8 WIRING DIAGRAMS.....	12



## Standard Features:

- High heat-transfer efficiency and low static-pressure drop A-shaped coil.
- Foil-faced insulation to prevent energy loss through the cabinet.
- Factory-sealed cabinet certified to achieve 2% or less air leakage rate at 1.0 inch water column.
- Multi-stage blower Speed Control to align with varying capacity demands.
- 4-position installation: Upflow, Horizontal Right, Downflow, Horizontal Left.
- Horizontal and vertical condensate drain pans standard, primary and secondary condensate fittings.
- Field-installed electric heater kits 5, 7.5, 10, 15, 20 kW available as accessories. Multiple electrical entry locations.
- Dual front panel, volute and coil with slide track, TXV with threaded connection for easy maintenance.
- Integrated filter rack with toolless door access.
- Easy-to-braze copper evaporator connection.
- TXV designed for easy piston replacement.
- All-aluminum heat exchanger extends product lifetime.
- Advanced internal welding process to reduce potential corrosion.
- AHRI and ETL listed.
- Polymer condensate drain pan with UVC inhibitor to extends product lifetime.
- Fully-insulated cabinet design.
- R454B refrigerant sensor ensures safe operation.
- R454B refrigerant sensor is factory-installed, making unit suitable for more room types and applications.

## 1 Product lineup

<b>Model</b>	MVMP18A1MN10OA MVMP24B1MN10OA MVMP36B1MN10OA MVMP48C1MN10OA MVMP60C1MN10OA
Power supply	208/230V-1ph-60Hz
Appearance	

## 2 Nomenclature

M	V	M	P	18	A1	M	N10	O	A
1	2	3	4	5	6	7	8	9	10

Legend		
No.	Code	Remarks
1	M	Brand: Midea
2	V	Vertical Air Handler
3	M	Multi Position installation
4	P	PSC Motor
4	18	Capacity: 18: 18 kBtu/h; 24: 24 kBtu/h; 36: 36 kBtu/h; 48: 48 kBtu/h; 60: 60 kBtu/h
5	A1	Cabinet Size
6	M	M: 208/230V 60Hz
7	N10	Refrigerant type: N10: R454B
8	O	O: Orifice (Piston) T: TXV
9	A	Design serial number

## 3 Specifications


	MVMP18A1MN100A	MVMP24B1MN100A	MVMP36B1MN100A
<b>NOMINAL RATING</b>			
Cooling (BTU/h)	18000	23000	34200
CFM (High/Low range)	600	900	1200
External Static Pressure (in.w.c) [Pa]	0.58 [145]	0.58 [145]	0.58 [145]
<b>ELECTRICAL DATA</b>			
Voltage / Phase(60Hz)	208V/230V-1ph-60Hz	208V/230V-1ph-60Hz	208V/230V-1ph-60Hz
Min. / Max. Voltage (V)	187/253	187/253	187/253
Min. Circuit Amps (MCA) (A)	1.8	2.5	3.3
Max. Overcurrent Protection (MOP) (A)	15	15	15
<b>FAN MOTOR</b>			
Motor Type	PSC	PSC	PSC
Capacitor (uF)	6	10	15
Horsepower (HP)	1/5	1/5	1/3
Rated RPM	755	820	980
Full Load Amps (FLA) (A)	1.4	2.0	2.6
<b>FAN BLOWER</b>			
Material	Metal	Metal	Metal
Type	Centrifugal	Centrifugal	Centrifugal
Diameter(in.) [mm]	10 [278.5]	10 [278.5]	10 [278.5]
Height(in.) [mm]	8 [207]	10 [271]	10 [271]
Coil Drain Connection FPT (in.)	3/4	3/4	3/4
<b>EVAPORATOR COIL</b>			
Type	Aluminum-Hydrophilic Aluminum	Aluminum-Hydrophilic Aluminum	Aluminum-Hydrophilic Aluminum
Tube Material	Aluminum	Aluminum	Aluminum
Tube Size (in.)	9/32	9/32	9/32
<b>SOUND POWER (dB)</b>			
	65	67	70
<b>REFRIGERANT CONNECTION SIZE</b>			
Liquid Line Size (O.D.) (in.)	3/8	3/8	3/8
Suction Line Size (O.D.) (in.)	3/4	3/4	3/4
<b>DIMENSIONS</b>			
Width (In.) [mm]	18-1/8 [460]	19-5/8 [500]	19-5/8 [500]
Height (In.) [mm]	41-3/8 [1050]	46-1/2 [1180]	46-1/2 [1180]
Depth (In.) [mm]	20-1/2 [520]	21-5/8 [550]	21-5/8 [550]
packaging dimension (W × H × D) (In.) [mm]	20-3/4 × 42 × 24-3/16 [527 × 1067 × 614]	22-5/16 × 47-1/8 × 25-3/8 [567 × 1197 × 644]	22-5/16 × 47-1/8 × 25-3/8 [567 × 1197 × 644]
<b>Service Valve</b>			
Liquid (in.)	3/8	3/8	3/8
Suction (in.)	3/4	3/4	3/4
<b>Weight</b>			
Net weight (lbs.) [kg]	108 [49]	130 [59]	130 [59]
Shipping weight (lbs.) [kg]	121 [55]	141 [64]	141 [64]

# High-Efficiency Air Handler



	MVMP48C1MN100A	MVMP60C1MN100A
<b>NOMINAL RATING</b>		
Cooling (BTU/h)	45000	54000
CFM (High/Low range)	1400	1650
External Static Pressure (in.w.c) [Pa]	0.58 [145]	0.58 [145]
<b>ELECTRICAL DATA</b>		
Voltage / Phase(60Hz)	208V/230V-1ph-60Hz	208V/230V-1ph-60Hz
Min. / Max. Voltage (V)	187/253	187/253
Min. Circuit Amps (MCA) (A)	4.3	5.0
Max. Overcurrent Protection (MOP) (A)	15	15
<b>FAN MOTOR</b>		
Motor Type	PSC	PSC
Capacitor (uF)	20	20
Horsepower (HP)	1/2	1/2
Rated RPM	900	980
Full Load Amps (FLA) (A)	3.4	4.0
<b>FAN BLOWER</b>		
Material	Metal	Metal
Type	Centrifugal	Centrifugal
Diameter(in.) [mm]	10 [278.5]	10 [278.5]
Height(in.) [mm]	10 [271]	10 [271]
Coil Drain Connection FPT (in.)	3/4	3/4
<b>EVAPORATOR COIL</b>		
Type	Aluminum-Hydrophilic Aluminum	Aluminum-Hydrophilic Aluminum
Tube Material	Aluminum	Aluminum
Tube Size (in.)	9/32	9/32
<b>SOUND POWER (dB)</b>		
	71	73
<b>REFRIGERANT CONNECTION SIZE</b>		
Liquid Line Size (O.D.) (in.)	3/8	3/8
Suction Line Size (O.D.) (in.)	7/8	7/8
<b>DIMENSIONS</b>		
Width (In.) [mm]	22 [560]	22 [560]
Height (In.) [mm]	51-1/2 [1385]	51-1/2 [1385]
Depth (In.) [mm]	24 [610]	24 [610]
packaging dimension (W × H × D) (In.) [mm]	24-11/16 × 55-3/16 × 27-11/16 [627 × 1402 × 704]	24-11/16 × 55-3/16 × 27-11/16 [627 × 1402 × 704]
<b>SERVICE VALVE</b>		
Liquid (in.)	3/8	3/8
Suction (in.)	7/8	7/8
<b>WEIGHT</b>		
Net weight (lbs.) [kg]	159 [72]	163[74]
Shipping weight (lbs.) [kg]	176 [80]	179[81]

## 4 Dimensional Drawing



Model Size	Unit Height "H" in. [mm]	Unit Width "W" in. [mm]	Unit Length "D" in. [mm]	Supply Duct "A"	Unit Weight (lbs.[kg])
18	41-3/8 [1050]	18-1/8 [460]	20-1/2 [520]	16 [406]	108 [49]
24	46-1/2 [1180]	19-5/8 [500]	21-5/8 [550]	18 [456]	130 [59]
36	46-1/2 [1180]	19-5/8 [500]	21-5/8 [550]	18 [456]	130 [59]
48	54-1/2 [1385]	22 [560]	24 [610]	19-1/2 [496]	159 [72]
60	54-1/2 [1385]	22 [560]	24 [610]	19-1/2 [496]	163 [74]

## 5 Electrical Characteristics

### Electric Heater Kit Breaker Information

NO.	Kit	Description	Breaker	Ref. Air Handler Use
1	EHK-05*	5kW Heater	Max. 240V, 30A, 2P	18, 24, 36, 48, 60
2	EHK-08*	7.5kW Heater	Max. 240V, 50A, 2P	18, 24, 36, 48, 60
3	EHK-10*	10kW Heater	Max. 240V, 60A, 2P	18, 24, 36, 48, 60
4	EHK-15*	15kW Heater, double breaker panel	Max. 240V, 50A, 2P	36, 48, 60
5	EHK-20*	20kW Heater, double breaker panel	Max. 240V, 60A, 2P	36, 48, 60



Note: Heater model number digits "\*": A, B, C, D, E, F, etc.



### Electric Heater Kit Electrical Data

Heater Kit Model Used	Air Handler Model	Electric Heat(kW)	Min. Circuit Ampacity (A)		Max. Fuse or Breaker (HACR) Ampacity (A)		Minimum Heating Blower Speed		
			240V	208V	240V	208V	Low	Medium	High
EHK-05*	18	5	26.1	22.6	30	25	●	●	●
EHK-08*		7.5	39.1	33.9	40	35	●	●	●
EHK-10*		10	52.1	45.2	60	50	●	●	●
EHK-05*	24	5	26.1	22.6	30	25	●	●	●
EHK-08*		7.5	39.1	33.9	40	35	●	●	●
EHK-10*		10	52.1	45.2	60	50	●	●	●
EHK-05*	36	5	26.1	22.6	30	25	●	●	●
EHK-08*		7.5	39.1	33.9	40	35	●	●	●
EHK-10*		10	52.1	45.2	60	50	●	●	●
EHK-15*	36	15	52.1/26.1	45.2/22.6	60/30	50/25	●	●	●
EHK-20*		20	52.1/52.1	45.2/45.2	60/60	60/50	●	●	●
EHK-05*		5	26.1	22.6	30	25	--	--	●
EHK-08*	48	7.5	39.1	33.9	40	35	--	--	●
EHK-10*		10	52.1	45.2	60	50	--	--	●
EHK-15*		15	52.1/26.1	45.2/22.6	60/30	50/25	--	--	●
EHK-20*	48	20	52.1/52.1	45.2/45.2	60/60	60/50	--	--	●
EHK-05*		5	26.1	22.6	30	25	●	●	●
EHK-08*		7.5	39.1	33.9	40	35	●	●	●
EHK-10*	60	10	52.1	45.2	60	50	●	●	●
EHK-15*		15	52.1/26.1	45.2/22.6	60/30	50/25	●	●	●
EHK-20*		20	52.1/52.1	45.2/45.2	60/60	60/50	●	●	●

Note: Heater model number digits "\*": L, M, N, O, P, Q", etc.

## Electric Heater Power Wiring Diagrams





## 6 Airflow Data

Model Number	Outdoor Unit Size (Ton)	Motor Speed		CFM Wet Coil Without Filter and Electric Heat									
				External Static Pressure (in w.c)									
				0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	
18	1.5	Low	Current / A	0.90	0.89	0.87	0.85	0.83	0.81	0.79	0.75	0.7	
			Power / W	207	203	198	191	187	182	173	162	151	
			CFM	649	618	586	548	509	467	420	350	283	
		Medium	Current / A	1.04	1.01	0.99	0.97	0.94	0.92	0.89	0.87	0.82	
			Power / W	243	236	230	224	218	210	204	198	184	
			CFM	815	796	758	720	677	624	573	522	421	
		High	Current / A	1.34	1.31	1.28	1.25	1.22	1.19	1.15	1.12	1.09	
			Power / W	313	305	297	289	280	270	259	250	242	
			CFM	945	933	897	855	811	757	692	633	566	
24	2	Low	Current / A	1.28	1.25	1.23	1.20	1.17	1.14	1.11	1.08	1.0	
			Power / W	289	281	274	265	253	244	234	223	206	
			CFM	1081	1028	977	909	796	714	628	539	407	
		Medium	Current / A	1.37	1.35	1.33	1.32	1.28	1.24	1.21	1.17	1.14	
			Power / W	315	309	303	297	287	274	263	252	242	
			CFM	1231	1176	1122	1068	976	851	757	659	552	
		High	Current / A	1.88	1.84	1.8	1.77	1.74	1.7	1.64	1.59	1.55	
			Power / W	423	409	399	389	380	364	344	329	314	
			CFM	1434	1371	1311	1249	1185	1081	922	807	689	
36	3	Low	Current / A	1.53	1.53	1.52	1.50	1.48	1.45	1.43	1.40	/	
			Power / W	323	319	314	307	294	281	268	251	/	
			CFM	1091	1048	1001	947	851	764	677	571	/	
		Medium	Current / A	1.72	1.71	1.7	1.68	1.67	1.64	1.62	1.59	/	
			Power / W	368	361	354	348	339	325	312	297	/	
			CFM	1335	1286	1230	1172	1103	986	866	752	/	
		High	Current / A	2.27	2.26	2.24	2.22	2.21	2.18	2.15	2.12	/	
			Power / W	473	462	452	442	430	419	399	383	/	
			CFM	1526	1467	1403	1335	1259	1181	1030	913	/	
48	4	Low	Current / A	2.30	2.25	2.21	2.18	2.14	2.10	2.05	1.92	1.85	
			Power / W	491	472	456	442	430	417	399	351	328	
			CFM	1496	1441	1383	1326	1273	1214	1137	872	746	
		Medium	Current / A	2.56	2.52	2.48	2.44	2.40	2.37	2.33	2.28	2.12	
			Power / W	562	548	535	523	509	497	482	465	410	
			CFM	1798	1731	1660	1597	1529	1452	1376	1283	921	
		High	Current / A	3.30	3.25	3.20	3.15	3.10	3.05	3.00	2.95	2.88	
			Power / W	704	689	673	656	640	624	610	593	570	
			CFM	1970	1896	1819	1737	1662	1580	1501	1411	1291	
60	5	Low	Current / A	3.09	2.95	2.87	2.81	2.73	2.66	2.58	2.48	2.2	
			Power / W	716	682	662	647	627	610	590	565	495	
			CFM	1872	1802	1747	1687	1628	1567	1500	1416	1140	
		Medium	Current / A	1.15	1.08	1.01	0.95	0.88	0.82	0.94	0.85	0.97	
			Power / W	751	729	711	694	675	657	638	617	592	
			CFM	2080	2012	1948	1886	1821	1753	1684	1604	1505	
		High	Current / A	3.70	3.60	3.53	3.42	3.34	3.26	3.17	3.08	2.99	
			Power / W	858	833	817	792	771	751	731	710	687	
			CFM	2198	2120	2068	1979	1908	1836	1760	1677	1584	

--- Shaded boxes represent airflow outside the required 300 to 450 cfm/ton, which are not recommended.

NOTES: Airflow based upon cooling performance at 230V with no electric heat or filter. Airflow at 208V is approximately the same as 230V because the multi-tap ECM motor provides constant torque with no drop off relative to motor operating speed.

# High-Efficiency Air Handler



The air distribution system has the greatest effect on airflow and is in the control of the installing contractor. For this reason, the contractor should use only industry-recognized procedures.

Heat pump systems require a specified airflow for electric heat operating. Each ton of cooling requires between 350 and 450 cubic feet of air per minute (CFM), or 400 CFM nominally.

Duct design and construction should be carefully done. System performance can be lowered dramatically through poor planning or workmanship.

Air supply diffusers must be selected and located carefully. They must be sized and positioned to deliver treated air along the perimeter of the space. If they are too small for their intended airflow, they would become noisy. If they are not located properly, they cause drafts. Return air grilles must be properly sized to carry air back to the blower. If they are too small, they also can cause noise.








Installers should balance the air distribution system to ensure sufficient, quiet airflow to all spaces to ensure maximum occupant comfort.

An air velocity meter or airflow hood can be used to balance and verify branch and system airflow (CFM).

## **IMPORTANT:**

1. If unit is converted to downflow, the airflow for model 18 must be between 350 and 450 cfm/ton.
2. When model 42 used for a mobile home, air volume should not be less than 1335 CFM.
3. When model 48 used for a mobile home, air volume should not be less than 1584 CFM.


## 7 Attached Fittings

Installation Fittings	Name	Appearance	Quantity	Name	Appearance	Quantity
	Indoor unit operation and installation manual		1	Sealing ring		3
	Accessory package		1	Alarm output wires		1
	Seal plug		2	Pipe Joint		1
	Hook		1			

Note: The above applies to most models however the list of included items may vary from model to model.

Before installation, confirm all the items above are present. Retain all these accessories for future use (if necessary). All fittings should be OEM factory fittings.

## 8 Wiring Diagram



**NOTES:**

- 1: Connect R to R, G to G, Y to Y, etc. See outdoor instruction for details.
- 2: If some signal lines of **CN36** are not used, please wrap them up separately with **CAP**.

**CAUTION:**

- 1: Use copper wire (75 °C min) only between disconnect switch and unit.
- 2: To be wired in accordance with **NEC** and local codes.
- 3: If any of the original wires, as supplied, must be replaced. Use the same or equivalent type wires.
- 4: If the input voltage is 208 V, please change the transformer tap by taking the red wire to **208V** terminal.
- 5: The rated operating condition of **Alarm** is 24 VAC/1A or 30 VDC/1A or 250 VAC/1A. Please refer to the manual for wiring methods.

LED1 STATUS	CONTENT	
	STEADY ON	NORMAL OPERATION
	OFF	POWER SUPPLY FAILURE
	KEEP FLASHING	REFRIGERANT LEAK PROTECTION
	3 FLASH/CYCLE	R454B REFRIGERANT SENSOR FAULT
	4 FLASH/CYCLE	R454B REFRIGERANT SENSOR COMMUNICATION FAULT
	8 FLASH/CYCLE	R454B SENSOR OVER SERVICE LIFE
Factory code	Date	Revision
16023000014749	Mar. 20th, 2024	D

**Midea Building Technologies Division**  
**Midea Group**

**Add.:** Midea Headquarters Building, 6 Midea Avenue, Shunde, Foshan, Guangdong, China

**Postal code:** 528311

[mbt.midea.com/global](http://mbt.midea.com/global)    [www.midea-group.com](http://www.midea-group.com)    [ics.midea.com](http://ics.midea.com)

Midea reserves the right to change the specifications of the product, and to withdraw or replace products without prior notification or public announcement. Midea is constantly developing and improving its products.

